

CLAM PRO RANGE PRO / PRO GPX





- Perfect heat & pressure distribution single electromagnetic plate of 40x50 cm
- Manual drawer on Clam Pro

User friendly:

- * Complete clearance of the plate
- * Automatic opening by electro-
- * Reversible C-shaped part & Quick Release
- Robust frame
- Suitable for laser transfer applica-
- sublimation on textile and rigid materials
- Ideal for small to medium productions
- Manufactured in France
- 2-year guarantee on the machine
- 10-year guarantee on heating element



Set programs



QuickRelease® system



GPX 3200W (Pro GPX version)




Pre-heat time

OPTIONAL ACCESSORIES



Support table



DTG plate



Set of 4 plates



Pressure selector



Teflon Sheet



Nomex® cover



Shoe plate



Email



Phone



Address









Office: + 33 4 68 74 05 89 Fax: + 33 4 68 74 24 08

SEFA SAS Z.I. PASTABRAC 11 260 ESPERAZA (FR)

TECHNICAL CHARACTERISTICS

Electromagnetic Type

Operation Slide - Tray with drawer, Clam -

Clamshell opening

40x50 cm / 16x20 " Platen size

Max thickness 15 mm

58 Kg / 128 lbs Weight Pressure 330 gr/cm² °C/°F Max 220 °C / 429 °F 2500 W (Pro) Power 3200 W (Pro GPX) Power supply

240 V Single-phase

Amperage 11 A (Pro)

14 A (Pro GPX)

Flex, Direct to Garment, Pretreat Applications

ment, Sublimation Rigid Subs trate, Textile Sublimation, Laser

Transfer, Screen Printing

969x990x453 mm Dimension

38x39x18 "

OPTIONAL ACCESSORIES




TAB-98 LITE Support table.



PLA-DRY M Sponge plate to dry pretreated clothes.




PLA-SET Set of 4 plates 12 x 8 cm, 15 x 15 cm, 12 x 45 cm, 25 x 30 cm.



PLA-SHOES-CV

Special plate that fits textile and sport shoes (side and back).



HOU-50

Heat resistant Nomex® cover for easier threading and protection.



OPT-2POS-CLAMPRO

Option to quickly change pressure from low to high (must be purchased simultaneously with the press).

SETTINGS



Electronics developed by Sefa

Accurate and fast regulation (PID control) for a wide range of heat transfer products: Flex, flock, sublimation, screen printing transfer.

Double timer (main + pre-heat)

2 cycle counters 3 settable programs

Stop cycle function

From 0 to 570 sec (precision +/- 1%). From 0 to 220°C (precision +/- 1%).

Heating time to reach 180°C: 15 min.



180° reversible C-shaped lower part with Quick Release system

DIMENSIONS

